





BIFACIAL MODULE WITH DOUBLE GLASS

WWW.RESUNSOLAR.COM



108 Cells

Mono N-type/Topcon MBB

550-590W

Power output


23.08%

The Highest Efficiency

0~+5W

Tolerance

0.5% Annual Degradation over 30 years



LINEAR PERFORMANCE WARRANTY

15 Year Product Warranty

30 Year Linear Power Warranty

RS9V-M-DG

RS9V-M-DG HALF-CELL series is produced with Topcon high efficiency MBB cells, which can reduce the module internal power loss to improve its conversion efficiency, as well as lower the failure risk caused by cracks and broken busbar to enhance the module reliability. Combined with half-cell technology, the module is highly resistant to hot-spot crisis caused by shadow effect.



High Reliability

Multi-busbar technology can effectively reduce the reliability risk caused by cells cracks and broken busbar.



Anti-PID Resistance

Prominent anti PID performance reduces the power degradation, leading to higher energy yield and lower LCOE.



Durability Against Extreme Conditions

Certified to resist high salt mist and ammonia conditions.



High Efficiency

Multi-busbar technology can reduce the module internal power loss to improve the module conversion efficiency significantly.



Low-Light Performance

With high transmittance and anti-reflective 2.0+2.0mm tempered glass, the module has stronger performance under low light circumstances.



High Mechanical Strength

Certified to withstand: high wind load(2400Pa) and snow load(5400Pa).

Full range of products and certification systems

ISO9001 TUV PID-FREE CEIEC61215/61730/61701/62716




RS9V-M-DG




GLOBAL PROFESSIONAL PV PRODUCTS INTEGRATED SOLUTIONS SUPPLIER


Dimension of PV Modules Unit: mm



I-V CURVES OF PV MODULE



P-V CURVES OF PV MODULE



ELECTRICAL DATA(STC)

Rated Power in Watts-Pmax(Wp)	550	555	560	565	570	575	580	585	590
Open Circuit Voltage-Voc(V)	38.65	38.85	39.05	39.25	39.45	39.65	39.85	40.05	40.25
Short Circuit Current-Isc(A)	18.13	18.18	18.23	18.28	18.33	18.37	18.42	18.47	18.51
Maximum Power Voltage-Vmp(V)	32.21	32.40	32.60	32.80	32.99	33.20	33.40	33.59	33.80
Maximum Power Current-Imp(A)	17.08	17.13	17.18	17.23	17.28	17.32	17.37	17.42	17.46
Module Efficiency	21.51%	21.71%	21.91%	22.10%	22.30%	22.49%	22.69%	22.88%	23.08%

STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.

ELECTRICAL DATA(NOCT)

Maximum Power-Pmax(Wp)	419	423	427	431	435	439	443	447	451
Open Circuit Voltage-Voc (V)	36.52	36.71	36.90	37.09	37.28	37.47	37.66	37.85	38.04
Short Circuit Current-Isc(A)	14.65	14.69	14.73	14.77	14.81	14.84	14.88	14.92	14.96
Maximum Power Voltage-Vmp(V)	30.28	30.46	30.64	30.83	31.01	31.21	31.40	31.57	31.77
Maximum Power Current-Imp(A)	13.84	13.89	13.93	13.98	14.03	14.07	14.11	14.16	14.19

NOCT: Irradiance at 800 W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

INTEGRATED PWER @ STC (REFERENCE TO 10%)

Rated Power in Watts-Pmax(Wp)	605	611	616	621	627	632	638	643	649
Open Circuit Voltage-Voc(V)	38.65	38.85	39.05	39.25	39.45	39.65	39.85	40.05	40.25
Short Circuit Current-Isc(A)	19.94	20.01	20.05	20.09	20.16	20.19	20.25	20.29	20.35
Maximum Power Voltage-Vmp(V)	32.21	32.40	32.60	32.80	32.99	33.20	33.40	33.59	33.80
Maximum Power Current-Imp(A)	18.78	18.86	18.90	18.93	19.01	19.04	19.10	19.14	19.20
Module Efficiency(%)	23.67%	23.90%	24.10%	24.29%	24.53%	24.72%	24.96%	25.15%	25.39%
BNPI/Isc(BSI)	22.48	22.54	22.61	22.67	22.73	22.78	22.84	22.90	22.95

MECHANICAL DATA

Solar cells	Mono-crystalline 210*105mm, 18/Busbars
Cell configuration	108cells(6*18)
Module dimensions	1962*1303*35mm/30mm
Weight	31.2kg/30.6kg
Front Cover	2.0+2.0mm Tempered Glass
J-BOX	IP68
Cable	4mm ² (IEC)/12AWG(UL), 300mm+300mm
Connectors	MC4 or MC4 Comparable

TEMPERATURE & MAXIMUM RATINGS

Nominal Operating Cell Temperature(NOCT)	45°C±2°C
Temperature Coefficient of Voc	-0.25%/C
Temperature Coefficient of Isc	0.045%/C
Temperature Coefficient of Pmax	-0.30%/C
Operational Temperature	-40~+85°C
Maximum System Voltage	1500V(IEC)/1500V(UL)
Max Series Fuse Rating	30A
Limiting Reverse Current	30A

PACKAGING CONFIGURATION

	40HQ
Modules per container	558/648pcs
Package	31/36pcs/pallet
Package Number	18pallets

Add: No.99 Zhidong Road, Zhixi Town, Jintan District, Changzhou, Jiangsu Province, China

Web: www.resunsolar.com

E-mail: info@resunsolar.com

Tel: +86 512-66292101 / +86 512-66293858